

# Index

- $(K, X)$ -bottleneck, 350
- $K$ -hop interference, 338
- $R^2$ , 372
- $\alpha$ -fair utility functions, 329
  
- access function, 344
- accountability, 126, 222
- Adaptive CSMA (A-CSMA), 345
- adaptive distance vector, 74
- admission management, 265
- advertising, 382, 386, 387, 389
- Amplified Spontaneous Emission (ASE), 15
- application-level mobility, 126
- architecture
  - nature of, 197, 199
- arrayed waveguide grating (AWG), 8, 10, 13, 19
- as-path, 246, 248–253
- augmentation, 340
- augmented model, 49
- autoconfiguration, 222, 233
- average rate region, 334
  
- $B/W$ , 156, 176
- bailout, 136, 139, 143–152
- BFS, 148
- BGP, 137, 139, 140, 142
- bi-directed networks, 361, 366
- biased feedback noise, 334
- Bit Error Rate (BER), 12
- Bit Torrent, 378
- bitrate, 20
- block scheduling, 370
- broadband access, 27
- broadcast, 361
- broadcast and select, 5
- buffer sizing, 270
- burst-mode receiver, 6, 16
  
- capability, 225
- CAPital EXPenditure (CAPEX), 18, 23
- case study, 213
- channel condition, 72
- channel diversity, 80
- channel ID (CID), 222
- channel switching delay, 80, 81
- channel, border, 227
- channels, 222
- channels, end-channels, 222
- channels, infrastructure-channels, 222
- charging, 259
- circuit switching, 3
- circuit-switching, 138
- cloud computing, 91
- coding advantage, 365–368
- CogNet layer, 78
- cognitive routing protocols, 72
- cognitive techniques, 72
- colorless ONU, 34
- Comcast, 378, 379
- computational resources, 94
- congestion, 239, 242, 253
- congestion control, 239
- connectivity, 362
- core optical switch, 174
- CORONET, 155
- cost fairness, 260
- critical message channel (CMC), 170
- cross-layer resource
  - allocator (CRA), 159
- crosstalk, 8, 11
  - coherent, 8, 9, 12
  - incoherent, 11
- cryptographic delegation, 124
- cryptographic hashes, 231
  
- data communications network, 44
- dedicated protection, 165
- design for change, 201, 205
- differentiated resilience, 65
- distributed computing, 88, 90, 95, 98
- domain-specific APIs, 293
- dual congestion controller, 335
- dynamic bandwidth allocation (DBA), 34
- Dynamic Host Configuration Protocol (DHCP), 235

- edge router failure, 65
- edge-to-edge, 138, 146
- EID-to-Locator (E2L), 224
- electronic domain, 3
- electronic label, 58
- endpoint IDs (EIDs), 222
- endpoints, 222
- excess loss, 11
- exponential rule, 349
- externality, 378, 394
- extinction ratio, 15, 16
  
- fabric, *see* Sensor fabric
- failure notification, 172
- federated approach, 172
- federation, *see* Sensor network federation
- Fiber cut, 66
- fiber-to-the-Home (FTTH), 28
- FIND program, 197, 198, 206, 208
- First-Fit on Shortest Path algorithm, 54
- fixed interface, 80
- forward price, 140, 144–146, 148–150
- forwarding, 219, 220
- forwarding directive(FD), 226
- forwarding nodes (FNs), 222
- free spectral range (FSR), 8
- FSS, 171
  
- game theory, 381, 390, 393, 394, 397
- generalized network utility maximization, 325
- Generalized-MPLS, 43
- GENI, 276
- GigE/WDM network, 50, 67
- gossip, 340
- granularity of restoration, 66
- graph partitioning, 340
- graph-coloring technique, 80
- greedy scheduling, 341
- grid, 88, 89
- grid architecture, 89
- grid computing, 88, 89, 91, 101
- grid functions, 89
  
- heavy-traffic analysis, 349
- HIP Architecture, 110
- HIP mobility, 121
- HIP multi-homing, 121
- Host Identity Protocol (HIP), 107
- Host Identity Tag (HIT), 112
- hot potato routing, 61
- hourglass, 201, 205
- hybrid provisioning, 52
  
- insertion loss, 10, 11
- Instantaneous parameters, 72
  
- integrated directed layered-graph, 56
- integrated routing, 49
- integrated routing algorithm, 52, 56
- integrated signaling, 49
- integrated signaling protocol, 58
- intelligent multi-interface selection function, 80
- intelligent multi-path selection function, 80
- inter-domain, 244, 245, 253
- interdomain routing, 62
- interference degree, 342
- Internet economics, 378, 380, 398
- Internet service classes, 399
- IP restoration, 65
- IP routing reconvergence, 64
- IP-layer mobility, 107
- IP/MPLS module, 58
- IP/MPLS router, 50
- IP/WDM architecture, 47
- IPv4/v6 interoperability, 107
- ISP Competition, 390
  
- joint scheduling, 95, 96, 98
  
- Kansas, University of, 220
- KanseiGenie, 278
- Kelly, 324
- Kentucky, University of, 220
- Kirchoff's laws, 393, 396
  
- label stack, 58
- lambda grid network, 90, 96, 98
- large deviation principle, 333
- large-deviation analysis, 349
- Layering As optimization Decomposition (LAD), 324, 326
- linecard, 3, 5
  - bitrate, 15
- link bundling, 44, 45
- link load, 72
- Link Management Protocol, 44
- link-based protection, 164
- link-state, 137, 139–142, 223
- local\_pref, 246, 249
- locally-greedy scheduling, 341
- locator, 224
- logical provisioning, 51
- logical topology, 51
- Long-Reach PON (LR-PON), 30
- loop-free, 244, 246, 248–250, 252, 253
- Lyapunov bound, 349
  
- marking function, 333
- Maryland, University of, 220
- max-weight, 339
- maximal scheduling, 341

- maximum saturated region, 342
- maxmin fairness, 329
- media streaming, 371
- mobility-aware routing protocol, 74
- monopolistic competition, 383
- motivation, 222, 223
- multi-channel capability, 79, 80
- multi-channel multi-interface routing protocol, 80
- multi-channel routing protocol, 83
- multi-homing, 107
- multi-hop logical links, 52
- multi-hop logical routing, 50
- multi-path routing, 238, 240, 241
- multi-Protocol Label Switching, 43
- multicast, 361
  
- Nash equilibrium, 384, 385, 388, 390–396
- NAT Traversal, 107, 123
- native Ethernet, 67
- Neighbor discovery, 44
- net-neutrality, 378, 380, 381, 383–386, 388–390
- network
  - virtualization, 208
- network access point, 61
- network coding, 359
- network element controllers (NEC), 161
- Network Management System (NMS), 160
- network resources, 92
- network service, 182
  - composition, 187
  - placement, 188
  - routing, 188
  - runtime management, 191
  - specification, 186
- network testbed, 92, 93
- Network Utility Maximization (NUM), 324
- network virtualization, 277
- network-network Interface, 46
- Network-Wide Exhaustive Search algorithm, 54
- neural network machine learning method, 77, 81
- New Internet Routing Architecture (NIRA), 234
- Nimrod Routing Architecture, 234
- noise figure, 14
- noise floor, 14, 15
- noise spectral density, 16
- NUM: interaction with HTTP, 333
  
- ontology, 207
- Open Shortest Path First protocol, 44
- optical access, 30
- optical amplifier, 17, 20
  - erbium doped fiber amplifier (EDFA), 7, 14, 16, 17, 20
  - semiconductor optical amplifier (SOA), 7
- optical burst switching, 89, 98, 100
- optical circuit switching, 89, 98
- optical cross-connect, 50
- optical domain, 4
- optical layer-based restoration, 65
- optical node architecture, 50
- optical signal-to-noise ratio (OSNR), 13, 16
- optimization, 203, 213
  - cross-layer, 202
  - cross-virtualization, 211
- optimization decomposition, 325
- Orca, 287
- other resources, 95
- overlay model, 48
- OXC controller, 49, 50, 58
  
- packet switch, 3
- packet switching, 3
- packet-level randomness, 332
- packet-switching, 136, 152
- packing, 362
- parallel-serial competition, 391
- parameter history, 72
- partial path, 226
- Passive Optical Network (PON), 28
- path fault, 226
- Path message, 46, 47
- path threading, 162
- path-based lightpath restoration, 66
- path-based protection, 164
- path-vector, 137, 139, 140, 142, 143
- peer model, 48
- peer-to-peer, 369, 378, 379, 398
- PHAROS, 156
- photronics in switching, 4
- physical impairment, 10
- physical provisioning, 51
- Pigovian tax, 394
- plane-switching (PS) architecture, 9, 18
- playbook, 166
- policy, 220
- Polynomial Time Approximation Scheme (PTAS), 347
- Postmodern Forwarding and Routing Infrastructure (PFRI), 220
- Postmodern Internet Architecture (PoMo), 220
- power consumption, 4
- power penalty, 10, 12
- pre-owned resources, 162
- predicted parameters, 72
- preemptive AODV, 74

- price of anarchy, 390, 391, 394, 396–399
- priority queueing, 399
- privacy, 126
- programmable fabric, *see* Sensor fabric, 276
- proportional fairness, 259, 260, 329
- protection paths, 47
- prototype, 232
  
- QoS, 136–140, 142, 143, 147, 152
  
- Random Early Detection (RED), 333
- random network coding, 371
- Randomized Pick and Compare, 339
- rate control protocol, 260, 261
- RDF, 207
- reactive optimization, 73
- realm, 227
- reducing unwanted traffic, 127
- Reflective ONU, 33
- regeneration, 10
- rendezvous server, 122
- rendezvous service, 122
- researcher portal, 288
- resource pooling, 241
- resource reservation, 280
- Resource Reservation Protocol, 46
- resource specification, 295
- restoration playbooks, 167
- Resv message, 46, 47
- reversible Markov process, 345
- risk, 136–138, 143, 144, 147, 149, 152
- risk-free, 145
- risk-neutral, 146, 152
- Rocketfuel, 147, 148, 152
- routine message channel, RMC, 170
- routing, 219, 220
- routing and wavelength assignment, 51
- Routing on Flat Labels (ROFL), 235
- routing state, packet-based, 222
- routing state, router-based, 222
- RSVP-TE, 46
  
- scalability, 4, 10, 16, 21, 24
  - switching bandwidth, 21
- scheduling, 88, 95
- scheduling algorithm, 5, 6, 9
  - centralized, 6
  - distributed, 6
- segment-based protection, 164
- semantics, 207
- sensitivity, 14, 16
- sensor fabric, 278, 284
- sensor network federation, 290
- sequential provisioning, 55
- service composition, *see* network service
- service differentiation, 398, 399
- service pipeline, *see* network service
- service specification, *see* network service
- session-level rate region, 328
- session-level stability, 329
- session-level stability: non-convex case, 331
- session-level stability: polytope and convex case, 330
- shared protection, 165
- Shortest path algorithm, 57
- Shortest Path Exhaustive Search algorithm, 53
- signaling and control network (SCN), 169
- SILO project, 197, 199, 201, 207
- single master, 161
- single-hop logical links, 52
- Slotted Aloha (S-Aloha), 342
- SOA gate, 7, 9, 14, 16, 20
- software defined optics, 211
- source independence, 368
- spectrum-aware routing protocol, 80
- spontaneous emission, 14
- state space collapse, 349
- Steiner tree, 365
- stochastic approximation, 346
- Stochastic Network Utility Maximization (SNUM), 324
- stochastic delay-difference equations, 332
- stochastic noisy feedback, 333
- stretching, 348
- sub-lambda grooming, SLG, 168, 174
- sub-lambda restoration, 66
- subnetwork mobility, 124
- switchable interface, 80
- switching capacity, 3
- switching fabric, 4, 5
  - optical, 5
- switching plane, 5–7, 15, 21
  
- Tassiulas and Ephremides, 334
- TE link, 44
- Tesseract, 235
- Thévenin equivalent, 395
- thin waist, 201, 205
- throughput, 361
- throughput increment, 74
- throughput maximization, 329
- throughput region, 338
- throughput-optimal, 339
- timescale difference, 336
- timescale separation, 329
- topological dynamics, 336
- topology abstraction, 158
- topology service (TS), 223
- traffic grooming, 52
- traffic increase, 3
- tragedy of the commons, 388

- 
- Trilogy project, 239, 253
  - TUN/TAP, 233
  - tunable laser, 20
  - tunable transmitter, 6, 13, 16, 20
  - tuning range, 6, 20
  - tussle, 136, 137, 152, 198
  - tussles, 220
  - two-sided market, 380
  
  - unbiased feedback noise, 334
  - unicast, 361
  - unified optical layer-based control model, 49
  - uniformity, 11
  - unitary resource management, 163
  - unwanted traffic reduction, 126
  - User-Network Interface, 46
  - utility function, 324
  
  - validation, 213
  - valley-free, 247, 251
  - value flow, 136, 152
  - VFSS, 166, 171
  - virtualization, 208
  
  - Wardrop equilibrium, 392
  - Wavelength Division Multiplexing (WDM),  
3, 5
  - Wavelength-routing (WR) architecture, 8, 17
    - Zero-Crosstalk, 8
  - Wavelength-selective (WS) architecture, 7,  
17
  - weight maximum independent Set (WMIS),  
339
  - weight maximum matching, 339
  - wireless Access, 36
  - wireless scheduling: problem tree, 337
  - wireless sensor network (WSN), 275
  - Wireless-Optical Broadband Access Network  
(WOBAN), 36