

---

## Index

- admissible solution, 268, 270–272, 274–276
- aggregated demand, 257
- all-optical circuit grooming, 284
- all-optical edge grooming, 286
- all-optical grooming, 279
- all-optical wavelength grooming, 280
- amplifier, 124
- arbitrary alternate routing, 208
  
- bandwidth-blocking probability (BBP), 112
- bi-directional path networks, 69
- bi-directional ring networks, 69
- blocking probability, 193
  - end-to-end, 201
  - fiber route, 203, 205
  - g-link, 195, 196, 201, 203, 205, 207
  - path, 195, 196, 201, 208
  - segment, 204, 205
  - wavelink, 196, 198
    - active call, 206
    - passive call, 206
  - waveroute, 195, 196, 200, 204
- BXC, 254–256, 260, 261, 269, 271, 272, 277
  
- call
  - active, 206
  - class, 198
  - multi-service, 198
  - passive, 206
  - service, 198
- carried load
  - fiber route, 204
  - g-link, 200
    - active call, 207
    - passive call, 207
  - path, 199
  - wavelink, 197, 200, 205
  - waveroute, 200, 205
- central office (CO), 107
- class- $\langle n, k \rangle$  call, 198
- complete lightpath cycle, 131
- complexity of Traffic Grooming, 57
- composite signal, 255
- connected lightpaths, 130
- control plane support
  - ASON, 21
    - mapping GMPLS, 26
  - call control, 31
  - hierarchical routing, 30
  - link resource manager, 28
  - mapping GMPLS, 27
  - model, 22, 26
  - resource discovery, 28
  - routing areas, 32
  - routing database, 28
  - subnetwork point, 26, 27
  - subnetwork point pool, 26, 27
  - UNI/NNI, 25
- GMPLS, 21
  - adaptation capability, 27, 28
  - bi-directional LSP, 31
  - bundling, 28
  - call control, 31
  - exchange point, 25

- explicit label, 31
- explicit route, 30, 31
- forwarding adjacency, 28, 30
- generalized label, 27, 31
- hierarchical routing, 30
- hierarchy, 22
- label set, 31
- link management, 22, 28, 29
- LSP, 22, 26
- mapping ASON, 26, 27
- MIB, 28
- model, 22, 26
- OPEX reduction, 21
- overlay/peer/augmented, 25
- resource discovery, 28
- routing protocols, 22
- RSVP-TE, 22
- signaling, 30
- signaling protocols, 22
- SRLG, 29
- support for VCAT/LCAS, 32
- switching capability, 27, 28
- TE link, 22, 26
- testbeds, 35
- upstream label, 31
- virtual link, 30
- grooming data plane
  - OTN, 22, 24
  - SONET/SDH, 22, 24
  - VCAT/LCAS, 24, 33, 34
- L1 VPN, 33
- PCE, 30, 34
- SLA/SLS, 33
- cost function, 261, 272
- cost per bit, 256
- crossbar switch, 17
  
- data centers, 253
- database backups, 253
- dedicated backup multiplexing, 152
- dedicated backup reservation, 150
- dedicated protection, 277
- demand time conflict reduction, 162
- dependable dynamic traffic grooming, 149
- deterministic, 254
- Digital Cross-Connect System (DCS), 15
- distribution
  - exponential, 111
  - Poisson, 111
- Dynamic Bandwidth Allocation (DBA), 51
- dynamic provisioning, 142
- dynamic restoration, 138
  
- electrical aggregation, 257
- electrical cross-connect, 254, 255
- electrical grooming, 254, 256, 257, 262, 272, 277
- End-to-end call loss probability, 196
- EXC, 254–258, 260, 262, 266, 277
  
- fiber channel (FC), 108
- fiber connection (FICON), 108
- Fiber Cross-Connect (FXC), 12
- fixed-point equation, 197, 201
  
- g-link, 194, 196
  - carried load, 197
  - repeated, 208
  - support, 195
  - topology, 194
- general shared path protection, 144
- Generic Framing Procedure (GFP), 52, 216
- generic framing procedure (GFP), 108
- grid networks, 69
- grooming, 254
- grooming and routing (GR), 123
- grooming lightpath, 257, 258, 263, 264, 272
- grooming link, 194
- grooming strategy, 256
- grooming switches, 15–19
- grooming, routing and wavelength assignment (GRWA), 124
  
- heuristics, 254
- hierarchical grooming, 73
  - clustering, 80
  - general topology networks, 77
  - hub selection, 80
  - lightpath grooming, 83
  - logical topology, 81
  - performance results, 84
  - ring networks, 74
  - RWA, 83
  - star networks, 76
  - torus networks, 76

- traffic routing, 81
  - tree networks, 76
- hierarchical grooming algorithm, 79
- I/O ports, 256, 260
- Integer Linear Programming (ILP), 124
- inter-office (IOF), 107
- inverse multiplexing, 108
- Lagrangian relaxation, 124
- light tree, 18
- light-trail, 155, 163
  - dynamic, 166
  - static, 164
- lightpath, 254–256, 260, 261, 265, 268, 269, 271, 272
- lightpath cycle, 131
- lightpath sequence, 194
- Line Terminal Equipment (LTE), 59
- linear programming, 254
- link capacity adjustment scheme, 108
- Link capacity Adjustment Scheme (LCAS), 51
- link protection, 277
- link-based protection, 140
- logical topology, 194
  - dynamic, 194
- management burden, 256
- Manhattan street networks, 69
- many-to-one traffic grooming, 227–232
  - exact approach, 229
  - heuristic approach, 231
- marginal demands, 258, 264
- matrix algebra, 263
- meta-heuristics, 254
- MG-OXC, 255, 260, 261
- mixed primary-backup grooming policy, 149
- monetary cost, 254
- Multi-Commodity Flow (MCF), 64
- multi-domain traffic grooming
  - conclusions, 251
  - introduction, 237
  - multi-domain standards, 238
  - open problems in multi-domain grooming, 245
  - research studies, 242
- multi-granularity switching, 255, 256
- multi-hop full grooming OXC, 17
- multi-hop partial grooming OXC, 18
- multi-layer, 255, 256, 262, 277
- Multi-Service Provisioning Platform (MSPP), 15
- multicast traffic grooming, 214–227
  - dynamic multicast traffic grooming, 223–227
  - enabling technology, 215
  - static multicast traffic grooming, 216–222
    - exact approaches, 216–220
    - heuristic approaches, 220–222
- multipoint traffic grooming, 213–233
  - types, 213
- network cost, 256, 261–264, 272, 277
- network design, 254
- network layer, 256, 261, 277
- node-edge incidence matrix, 126
- nominal capacity, 257
- NP*-Complete, 112
- NP-complete, 123
- objective function, 261
- OEO cost, 60
- offered load
  - active call, 206
  - g-link, 200
  - passive call, 206
  - segment, 204
  - wavelink, 196, 200, 205
  - waveroute, 197
- optical burst switching (OBS), 287
- optical cross-connects, 137
- Optical Cross-Connects (OXC), 12
- optical crossconnect (OXC), 113
- optical grooming, 254, 256, 260–262, 268, 270, 274, 277
- optical layer, 125
- optical node architectures, 9–19
- optical packet switching (OPS), 287
- optical switching, 13
- optical time-division multiplexing (OTDM), 284
  - principle, 285
- optical transport network (OTN), 108
- optimisation techniques, 254
- opto-electronic, 256

- p-cycle protection, 141
- partial protection, 153
- partition, 270
- path protection, 277
- path restoration algorithm, 142
- path-based protection, 140
- performance model, 193
- permanent connection, 256
- permanent demands, 254
- physical layer, 125
- planning, 254
- point-to-point protocol (PPP), 108
- power, 269
- pre-cross-connected shared path protection, 145
- preplanned protection, 138
- protection design, 143
- provisioning, 254, 256, 273
  
- random traffic demands, 253
- random traffic grooming, 209
- random wavelength assignment, 208
- Reconfigurable OADM (ROADM), 280
  - multi-degree, 282
- reduced load approximation, 194, 196
- restricted sharing admission, 196, 198
- Routed Scheduled Band Group, 261, 270, 274
- router, 255
  
- scheduled demands, 253, 254, 277
- scheduled electrical demands, 254
- scheduled lightpath demands, 254, 268
- scheduled services, 158
- SED, 254, 256, 257, 262–265, 267, 272, 273, 277
- segment, 203
- segregated primary-backup grooming policy, 149
- self-routing fabric, 17
- service- $k$  call, 198
- set-up date, 253, 254, 261–263, 268
- shared backup multiplexing, 151
- shared backup reservation, 150
- shared bus, 16
- shared memory, 17
- shared protection, 277
- shelf, 269
- shortest path, 256, 262, 263, 268, 272
  
- single-hop grooming OXC, 17
- single-layer, 256
- SLD, 254, 256, 261, 262, 267–271, 274, 277
- sliding scheduled traffic model, 160
- Soft Failure, 52
- solution space, 270
- SONET/SDH Rings, 91
  - arbitrary traffic, 105
  - Bidirectional Line-Switched Ring (BLSR), 91
  - fixed traffic
    - bounds, 93
  - hubbed rings, 95, 98
  - multi-ring topologies, 98
  - Unidirectional Path-Switched Ring (UPSR), 91
- SONET/SDH rings, 105
  - arbitrary traffic, 98
  - fixed traffic, 92–98
    - algorithms, 97–98
    - bounds, 97
  - incremental traffic, 104
- source-edge incidence matrix, 126
- spider networks, 69
- star networks, 69
- state-of-the-art, 256
- static traffic grooming with min-max objective, 71
- statistical multiplexing gain (SMG), 11
- storage-area network, 108
- subgraph-based routing, 140
- subgraph-based routing strategy, 141
- subwavelength demands, 253–256
- survivability, 138
- switch ports, 254
- switching fabric, 255, 256
- switching granularity, 253
  
- tear-down date, 253, 254, 261–263, 268, 277
- time diagram, 257, 272, 273
- time-disjoint, 254, 277
- topology, 254, 257, 260–263
- traffic grooming, 157
  - dynamic, 193
  - multi-hop, 194
  - policy, 206
  - single-hop, 194

- static, 193
- traffic pattern, 111
- traffic types, 91
- transit traffic, 256
- transponder, 11, 124
- transponders, 254
- tree networks, 71
- tuple, 254, 261
- uncertainty, 254, 277
- unidirectional path networks, 62
- unidirectional ring networks, 69
- ventilation system, 269
- virtual concatenation, 108
  - (VC), 109
- Virtual Concatenation (VCAT), 49
- Virtual concatenation group (VCG), 49
- waveband, 253–256, 260, 261, 271, 272
- waveband cross-connect, 254, 255
- waveband switching, 261
- waveband-switching connection, 260, 261, 268, 271
- wavelength, 255
- wavelength assignment, 260
- wavelength assignment (WA), 123
- wavelength capacity, 125
- wavelength continuity, 126
- wavelength continuity constraint, 260
- wavelength conversion, 203, 260
- wavelength cross-connect, 254, 255
- Wavelength Interchanging Cross-Connect (WIXC), 13
- Wavelength Selective Cross-Connect (WSXC), 13
- Wavelength-Band Cross-Connect (WBXC), 12
- wavelink, 195, 196, 198
  - repeated, 203, 208
- wavelink blocking model, 198
- waveroute, 195, 196, 198, 203
- WDM grooming, 193
- wavelength network topologies, 61
- WXC, 254–256, 258, 260–262, 266, 269, 272, 277